

DF-350A

SURGICAL & GYNECOLOGY SUCTION UNIT



The outer shell of the instrument adopted by ABS material. Clear simple lines and nice looking appearance create a new enjoyment for users. Humanized design with outstanding technology impressed users in medical institutions, clinics, nursing homes and health care facilities.

Benefits

- The vacuum pressure may be easily read through the vacuum gauge.
- The suction bottle is made by PC which is reusable and autoclavable. It features with carrying handle which is easy to lift and transport.
- 360° moving caster with locking brake features easy movement and high safety.
- The fastening rack installed at side of machine for hanging suction tube.
- Surgical suction function features with smaller caliber which is ideal for general vacuum.
- Obstetrical suction function features with both small and large calibers. It is ideal for doing artificial abortion by using bigger caliber. Smaller caliber can be used to suck baby out with suction cups.
- Surgical & OBS. Select Valve on the panel can be switched. Two functions features in one machine is convenient and time efficient.
- The fan installed at the back of machine helps to reduce the heat.
- The machine equipped with foot switch, user may choose manual or foot control.
- The capsule shaped floating control may fully prevent overflow by any angles, and the angle pipe may lead the water fluently.

Standard Accessories

| Suction tube (S) 180cm | 2pcs |
|------------------------|------|
| Suction tube (L) 180cm | 1pc |
| Suction catheter | 1pc |
| Foot switch | 1pc |
| Filter (L) | 2pcs |
| Adaptor (D) | 1pc |
| Detachable square tray | 1pc |

Angle pipe (L) 3000 c.c. PC bottle

Select valve (OBS, & Surgical)

Safety device (L)

OBS suction adapter

Filter (L)

Caster with locking brake

Specification

| > 650 mmHg |
|-----------------------|
| 80 L / min |
| 3000 c.c. + 3000 c.c. |
| 19.5 / 25 kg |
| L45 x W35 x H84 (cm) |
| L54 x W44 x H96 (cm) |
| |

Power switch (ON/OFF)

Foot switch

Vacuum gauge

Regulator valve

Tube holder

Surgical suction adaptor

Angle pipe (S)

Safety device (S)

Adapter of foot switch

Circuit breaker

90-026

Oil-less Twin Cylinder Piston Vacuum Pump

\$ 100007581BIC pr.mov



Thermal protector, auto reset.



| Voltage | 120V / 240V |
|----------------|-------------|
| Current | 2.2A / 1.1A |
| Capacitor | 26uf / 13uf |
| R.P.M. | 1720 |
| Poles | 4 |
| Output | 250W, 1/3HP |
| Max. Flow rate | 80 L/min |
| Max. Suction | > 650mmHg |
| Welght | 8.2 kg |
| | |



