

SURGICAL SUCTION UNIT (Aspirator)

NEW TYPE

Whole A.B.S plastic injection made outer shell.



DF-650

CE 2460

ISO 9001

ISO 13485

**Growing with
Creativity Sincerity
Service**



DOCTOR'S FRIEND medical instrument co., ltd.

SURGICAL SUCTION UNIT

Quality Speaks Itself

DF-650


1. The outer shell of the instrument adopted by ABS material. Clear simple lines and nice looking appearance create a new enjoyment for users. Humanized design with outstanding technology impressed users in big hospitals, medium/small clinics, nursing homes and home cares.
2. Adhering to the concept of environmental protection, ecological protection and economical benefits makes each item of material be recycles as possible as it can to reduce waste and protect natural resource.

Functions:

- Digital Vacuum Monitor is used to show the suction power, so users can easily read it.
- The suction tube directly connects to the suction bottle, so users can easily wash it. It's sanitary & safe.
- The handle attached to the suction bottle makes users easily lift and wash it.
- The foot switch adopts air pressure type, so it's anti-moisture, insulating & safe.
- 360° Individual brake wheel features easy movement and high safety.
- The fastening rack installed at the side makes the suction tube be easily put.

The Instrument plane :

- 1 Digital vacuum monitor
- 2 Regulator valve
- 3 Surgical tube holder
- 4 Surgical suction adapter
- 5 3000 c.c. bottle
- 6 Power switch (On/Off)
- 7 Filter (L)
- 8 Floating control (L)
- 9 Floating control (S)



Standard accessories

1. Suction tube (S) 180cm 1 pc
2. Suction catheter.....1 pc
3. Foot switch.....1 pc
4. Filter2 pcs
5. Square tray 1 pc


Specifications

Max. HP 250 W 1/3 HP
Vacuum Range >650 mmHg
Max. Flow 80 L /min
Capacity 3000c.c. x 2 pcs
Foot control Air pressure type
Machine Size L45xW35xH84 cm
Machine Weight 19 kg

The Side:

- 1 Power cord
- 2 Adapter of foot switch
- 3 Circuit breaker
- 4 All casters with locking brakes
- 5 Foot switch (Air pressure type)

OIL-LESS VACUUM PUMP (90-026) Twin cylinder piston pump design.



Humanizing design:
Low noise, Wear resistance.

Compact structure:
Low power consumption, long life.

Fully oil-less:
Non-pollution, free maintenance.

Pump specification

Voltage	120V	240V
Current	2.2A	1.1A
Capacitor	26uf	13uf
R.P.M.	1720	
Poles	4	
Output	250W 1/3HP	
Max. flow rate	80 L/min	
Max. suction	>650 mmHg	
Weight	8.2 kg	

Thermal protector, auto reset



- 1 Fix cover
- 2 Depositing box
- 3 Fan



DOCTOR'S FRIEND medical instrument co., Ltd.