

ri-focus® LED
WIRELESS HIGH PERFORMANCE LED HEADLIGHT
POWERED BY LI-BATTERIES OR RECHARGEABLE BATTERIES

green efficiency

ri-focus® LED
 With 1 set of CR 123 A
 lithium batteries
 Art. No.: 6090

With 1 set of NiMH
 rechargeable AAA
 batteries and plug-in
 charger
 230 V Art. No.: 6091
 120 V Art. No.: 6092

Plug in chargers
 230 V Art. No.: 11284
 120 V Art. No.: 11286

Batteries
 Lithium CR 123 A
 2 pcs Art. No.: 11287
 AAA NiMH
 rechargeable batteries
 4 pcs Art. No.: 11288

Foam-rubber band
 120 mm long Art. No.:
 11289

Fabric points
 Ø 35 mm Art. No.: 11293
 Ø 47 mm Art. No.: 11294

Battery compartment
 cover
 For lithium CR 123 A
 Art. No.: 12680
 For AAA NiMH
 rechargeable batteries
 Art. No.: 12681

- **One hand operation**
 - **Wireless and balanced headband with built in battery compartment**
 - **More efficient diagnosis due to white high performance LED (140 lumen)**
 - **Service life of LED up to 50.000 hours**
 - **Significantly less energy consumption and heat generation**
- Headband version, with built-in battery compartment and integral charge jack, can be optionally fitted with 2 lithium batteries size CR 123 A, 4 batteries size AAA (alkaline) or 4 rechargeable batteries size AAA (NiMH).
 - Headband cleaning made easy by inner, removable and washable padding.
 - Particularly comfortable with balanced, infinitely adjustable headband.
 - On/off switch on battery compartment.
 - Charge jack for plug-in charger integrated in battery compartment.
 - Focusable LED lamp at a distance of 40 cm /15.75 inch approx. Ø 40 mm /1.57 inch - Ø 200 mm / 7.87 inch, infinitely adjustable.
 - White LED with 6.500 Kelvin.
 - Battery operation: approx. 4 hrs. with lithium batteries, approx. 90 min. with alkaline batteries Type AAA.
 - Rechargeable battery operation: approx. 90 min. with fully charged battery.
 - Weight: 210 g / 0.46 lb without batteries, 242 g / 0.54 lb with CR 123 A lithium batteries, 259 g / 0.57 lb with rechargeable AAA batteries.



Distance	400 mm / 15.75 inch	200 mm / 7.87 inch
Lux max	10.000	23.000
Circle of light max. Ø	200 mm / 7.87 inch	120 mm / 4.73 inch
Circle of light min. Ø	40 mm / 1.57 inch	30 mm / 1.18 inch