

SURGICAL SUCTION UNIT (Aspirator)






DF-650A

SURGICAL SUCTION UNIT

The Best Just Got Better.



Benefits

- The vacuum pressure may be easily read through the vacuum gauge.
- The suction bottle is made by PC which is reusable and autoclavable. It features with carrying handle which is easy to lift and transport.
- 360° moving caster with locking brake features easy movement and high safety.
- The fastening rack installed at side of machine for hanging suction tube.
- The fan installed at the back of machine helps to reduce the heat.
- The machine equipped with foot switch, user may choose manual or foot control.
- The capsule shaped floating control may fully prevent overflow by any angles, and the angle pipe may lead the water fluently.

Specification		
Vacuum Range	> 650 mmHg	
Max. Flow	80 L / min	
Capacity	3000 c.c. x 2 pcs	
N.W. / G.W.	20.5 / 25.5 kg	

Machine size

Packing size

L45 x W35 x H84 (cm)

L54 x W44 x H96 (cm)

Standard	Accessories

Suction tube (S) 180cm	1pc
Suction catheter	1pc
Foot switch	1pc
Filter (L)	2pcs
Detachable square tray	1pc

		1.01	4.0
Pum	p spe	CITICS	ation
ı unı	σ σ	CHIC	αιισπ

Voltage	120V / 240V
Current	2.2A / 1.1A
Capacitor	26uf / 13uf
R.P.M.	1720
Poles	4
Output	250W, 1/3HP
Max. Flow rate	80 L/min
Max. Suction	> 650mmHg
Weight	8.2 kg

90-026

Oil-less Twin Cylinder Piston Vacuum Pump



Thermal protector, auto reset.





