



## H3V 3-Channel Electrocardiograph

---

Display:  
6.2" LCD touch screen (resolution:600 × 480)  
3 × 4 and 6 × 2 display format, 12-lead waveforms display simultaneously;  
Intelligent brightness sensor for automatic screen brightness adjust

**COMEN**

## Recording and Data printing

- 80mm × 20m Roll paper or Z-fold paper
  - Built-in thermal printer / Optional: external printer
  - Recording format:
  - Built-in printer: 3 × 4、3 × 4+1R
  - External printer: 3 × 4、3 × 4+1R、3 × 4+3R、6 × 2、6 × 2+1R、12 × 1、12 × 1+T
  - 10,000 ECG built-in records with binary image format
  - Connectable with FTP server for patient data remote-control
  - Connectable with PC-based ECG management software
  - Unlimited USB data transfer
- Recording Mode
    - a) Default Print: in automatic mode, ECG waveform is printed.
    - b) One-key manual print: By pressing “print” again, rhythm-lead report is printed manually after the default full information report;
    - c) Extendable print: In case arrhythmia occurs, rhythm-lead report is automatically printed after the default full information report.

- 1/3 channel rhythm lead display
  - Support R-R (rhythm) analysis function
  - Support real-time sampling and pre-sampling
  - Support synchronous sampling and sequential sampling
  - Pace-maker detection
  - ECG review, 600 seconds waveforms review and print for any 12 leads within 10 seconds
- Automatic standby and timing on-off function
  - Li-thium battery
  - Scanner connectable
  - Smart touch screen with slide and multi-finger operate function
  - Smart name and fuzzy ID search function



CE 0120

**Shenzhen Comen Medical Instruments Co., Ltd.**

P/N: EN-H3-2P-20190528-V1.0

Add: No.2 of FIYTA Timepiece Building, Nanhuan Avenue, Gongming Sub-district, Guangming New District, Shenzhen, 518106, P.R.China  
Tel: +86-755-2640 8879 Fax: +86-755-2643 1232 Website: en.comen.com E-mail: info@szcomen.com